

The odsfile package: accessing of the opendocument spreadsheet from \LaTeX documents*

Michał Hoftich (michal.h21@gmail.com)

September 7, 2023

Contents

1	Introduction	1
2	Usage	2
2.1	Character escaping	5
3	Templates	6
4	Adding data	6
5	Loading and saving of the ods file	7
6	Lua library	7
7	Changes	9

1 Introduction

This is Lua \LaTeX package and lua library for working with opendocument spreadsheet (ods) documents from Open/Libre Office Calc. Their contents can be read as \LaTeX tables, can be pass to macros, you can also add new data to existing spreadsheets.

The ods format consist of number of xml files packed in the zip file. This package uses Lua \TeX 's zip library, LuaXML library¹ and lua scripting to read xml content from this archive, which means that it is not possible to use this package with pdf \LaTeX or Xe \LaTeX . On the other side, odsfile.lua library can be used from Plain \TeX , ConTeXt or pure lua scripts.

Creation of this package was motivated by question² on site <http://tex.stackexchange.com/>. Development version of the package can be found at

^{*}Version 0.8, last revisited 2023-09-07.

¹Pure lua library for working with xml files, it is available form CTAN or <https://github.com/michal-h21/LuaXML>

²<http://tex.stackexchange.com/questions/60378/insert-libreoffice-table-as-input>

<https://github.com/michal-h21/odsfile>, all contributions and comments are welcome.

2 Usage

You can load odsfile classically with

```
\usepackage{odsfile}
```

There are macros:

- \includespread
- \includespread*
- \OdsN1
- \OdsLastN1
- \tabletemplate
- \loadodsfile
- \savespreadsheet
- AddRow environment

\includespread

Main command is \includespread and it's starred variant \includespread*.

It's syntax is:

```
\includespread[(key-value list)]
```

Options are:

file Filename of file to be loaded. You should specify this only on first use of \includespread.

sheet Name of sheet to be loaded. If it's not specified on first use of \includespread, then first sheet from the file is loaded. The sheet remains selected until another use of sheet.

First	2,2
Second	3,1

```
1 \begin{tabular}{l l}  
2 \includespread[file=pokus.  
ods,sheet=List2]  
3 \end{tabular}
```

range Selects range from table to be inserted. Range is specified in format similar to spreadsheet processors, like a2:c4, selecting cells starting at first column, second row and ending and third column, fourth row. Other variant of supported ranges are *named ranges*, which can be saved in the ods file.

Hello	1	3
World	2	4
AA	3	5

```
1 \begin{tabular}{lll}  
2 \includespread[sheet=List1,  
range=a2:c4]  
3 \end{tabular}
```

You can omit some or both of the numbers:

Label	Position	Count
Hello	1	3
World	2	4
AA	3	5

```

1 \begin{tabular}{lll}
2 \includespread[range=a:c4]
3 \end{tabular>

```

Label	Position
Hello	1
World	2
AA	3
BB	4
CC	5
\textbf{bold}	6

```

1 \begin{tabular}{ll}
2 \includespread[range=a:b]
3 \end{tabular>

```

1	3
2	4
3	5
4	6
5	7
6	8

```

1 \begin{tabular}{ll}
2 \includespread[range=b2:c]
3 \end{tabular>

```

AA	3	5
BB	4	6
CC	5	7

```

1 \begin{tabular}{lll}
2 \includespread[range=
    newrangetest]
3 \end{tabular>

```

columns Column heading specification. It can be either head, top, or comma separated list of values.

top Use as headers first line from the table.

Position	Count
2	4
3	5
4	6

```

1 \begin{tabular}{ll}
2 \includespread[range=b3:c
    ,columns=top]
3 \end{tabular>

```

Note that if you include whole table, first line is included twice:

Label	Position	Count
Label	Position	Count
Hello	1	3
World	2	4
AA	3	5
BB	4	6
CC	5	7
\textbf{bold}	6	8

```

1 \begin{tabular}{lll}
2 \includespread[columns=
    top]
3 \end{tabular>

```

in this case you can use

head use first row from selection as headings.

Label	Position	Count
Hello	1	3
World	2	4

```

1 \begin{tabular}{lll}
2 \includespread[columns=
               head,range=a:c3]
3 \end{tabular}
```

manually specified list If column headings are not specified in the file, you can set them manually.

title	amount
First	2,2
Second	3,1

```

1 \begin{tabular}{ll}
2 \includespread[columns={title,amount},sheet=
               List2]
3 \end{tabular}
```

columnbreak Command inserted in manual linebreaks in cells. Default value is `\linebreak`

rowseparator Rows are normally separated with newlines, if you really want, you can separate them with `hlines`.

Possible values:

tableline (default) Inserts `\\" character`

hline Inserts `\\" \\hline`

newline Inserts blank line

user specified separator useful in conjunction with **rowtemplate** (p. 5), for example if you want to include sheets as plaintext or input for plotting functions.

Label	Position
Hello	1
World	2
AA	3
BB	4

```

1 \begin{tabular}{ll}
2 \includespread[columns=top,
               sheet=List1,
               rowseparator=hline,
               range=a2:b5]
3 \end{tabular}
```

template Templates are simple mechanism to insert whole tabular environment with column specification. All columns are aligned to the left, if you want to do more advanced stuff with column specifications, you must enter them manually as in all previous examples.

Label	Position	Count
World	2	4
AA	3	5
BB	4	6
CC	5	7
<code>\textbf{bold}</code>	6	8

```

1 \includespread[columns=top,
               template=booktabs,range
               =a3]
```

For more info about templates, see next section 3

coltypes When using template, column types are inferred automatically. If that doesn't work well in your case, you can specify them manually with `coltypes` option.

Label	Position	Count
Hello	1	3
World	2	4
AA	3	5
BB	4	6
CC	5	7
\textbf{bold}	6	8

```

1 \includespread[columns=
  head, template=
  booktabs, coltypes=
  lrr]
```

rowtemplate Enables to convert tabular data to something different than L^AT_EX tables. Syntax for rowtemplates is similar to the table templates, variables are inserted with `-{number}`, where number is the position of the cell from beginning of the selection.

<i>Hello:1, World:2, AA:3, BB:4, CC:5,</i> <i>\textbf{bold}:6</i>	<pre> 1 \includespread[range=a2:b, rowseparator={, \ }, rowtemplate={\textit {-{1}}:-{2}}]</pre>
--	--

celltemplate This template is applied to every cell in the included table.

Label	Position	Count
Hello	1	3
World	2	4
AA	3	5
BB	4	6
CC	5	7
\textbf{bold}	6	8

```

1 \begin{tabular}{lll}
2   \includespread[range=a
    1:c1, celltemplate
    ={\textit{-{value
    }}}]
3   \includespread[range=a
    2:c]
4 \end{tabular}
```

multicoltemplate supports merged cells. Default template uses left aligned `\multicolumn` command

Hello world table with merged
--

```

1 \begin{tabular}{lll}
2 \includespread[sheet=
  Sheet3,
  multicoltemplate={\multicolumn{-{count}}{r}{-{value}}}]
3 \end{tabular}
```

2.1 Character escaping

To prevent compilation errors, odsfile escapes characters that have special meaning in L^AT_EX, for example backslashes or dollar characters. In some cases, you may want to execute the T_EX code that is saved in the spreadsheet. In that case, use the `escape` option:

escape Set the value to false to ignore special characters in the cell data.

The following example prints the left cell in the last row in table in bold, because the original spreadsheet contains the \textbf{bold} command.

Label	Position	Count
Hello	1	3
World	2	4
AA	3	5
BB	4	6
CC	5	7
bold	6	8

```
1 \begin{tabular}{lll}
2 \includespread[sheet=List1,
    columns=head, escape=false]
3 \end{tabular}
```

3 Templates

If you don't want to specify tabular environment by hand, you can use simple templating mechanism to insert tabular environment by hand.

Templates are defined with macro

```
\tabletemplate{<template name>}{<template code>}
```

there is default template:

```
\tabletemplate{default}{-{colheading}-{rowsep}-{content}}
```

Code `-{variable name}` inserts one of the following variables:

coltypes This is code to be inserted in `\begin{tabular}{coltypes}`. The p column specifier is used for each column, where cell with manual line break occurs, l is used otherwise.

colheading Column headings.

rowsep It inserts row separator defined with rowseparor key of `\includespread`. It is used in default style to delimit column headings and table contents.

content Tabular data.

More powerful template for the booktabs package

```
\tabletemplate{booktabs}{%
\begin{tabular}{-{coltypes}}
\toprule
-{colheading}
\midrule
-{content}
\bottomrule
\end{tabular}
}
```

4 Adding data

There is simple interface for adding new rows to the spreadsheet.

AddRow [*row number*] environment for adding new row to the current sheet. Optional argument [*row number*] specifies where it should be inserted, if blank, it will be inserted at end.

Inside AddRow, you can use

- \AddString{*text*} {*position*}
- \AddNumber{*number*} {*position*}

Position specifies cell, where data should be added, if you leave it blank, it will be laced next to the previous one.

Label	Position	Count
Hello	1	3
World	2	4
AA	3	5
BB	4	6
CC	5	7
\textbf{bold}	6	8

Label	Position	Count
Hello	1	3
third row	22	
World	2	4
AA	3	5
BB	4	6
CC	5	7
\textbf{bold}	6	8
last row		

```
1 \includespread[columns=head,
                 template=booktabs]
2 \begin{AddRow}
3   \AddString{last row}{}
4 \end{AddRow}
5 \begin{AddRow}[3]
6   \AddString{third row}{}
7   \AddNumber{22}{2}
8 \end{AddRow}
9 \includespread[columns=head,
               template=booktabs]
```

5 Loading and saving of the ods file

You can explicitly load ods file with \loadodsfile[*key val list*] {*filename*}. This can be useful, if you only want to write some data to the file, otherwise it is better to use \includespread.

For saving spreadsheets modified with AddRow, you can use \savespreadsheet. This command uses call to external zip utility, so you should have installed it and you have to call **LuaLaTeX** with lualatex --shell-escape filename. **LuaLaTeX** also must have write permissions for accessing the ods file. This command creates file content.xml in the current directory, so if external call fails, you can run

```
zip -r filename.ods content.xml
```

by hand.

6 Lua library

The lua library uses luazip library integrated to LaTeX and LuaXML³, pure lua library for working with XML files.

To use library in your code, you can use:

```
require("odsfile")
```

Function odsfile.load(filename) returns odsfile object, with loadContent() method, which returns lua table representing content.xml file. We can select sheet from the spreadsheet with odsfile.getTable(xmlobject,sheet_name). If we omit sheet_name, first sheet from spreadsheet is selected.

Data from sheet can be read with odsfile.tableValues(sheet, x1, y1, x2, y2). x1 - y2 are range to be selected, they can be nil, in which case whole rows and cells are selected. For converting of standard range expressions of form a1:b2 to this representation, function odsfile.getRange(range) can be used.

Example usage – file odsexample.lua

```
require "odsfile"

-- Helper function to print structure of the table
function printable(tb, level)
    level = level or 1
    local spaces = string.rep(' ', level*2)
    for k,v in pairs(tb) do
        if type(v) ~= "table" then
            print(spaces .. k..'= '..v)
        else
            print(spaces .. k)
            level = level + 1
            printable(v, level)
        end
    end
end

local ods = odsfile.load("filename.ods")
local f, e = ods:loadContent()

-- Get First sheet from the table
body= odsfile.getTable(f)
-- Print structure of the range a4:b5
printable(odsfile.tableValues(body,odsfile.getRange("a4:b5")))
```

Run the example with texlua odsexample.lua from the command line, you should get following result:

```
1
 1
  value=AA
  attr
    office:value-type=string
```

³<https://github.com/michal-h21/LuaXML>

```

2
  value=3
  attr
    office:value-type=float
    office:value=3
2
1
  value=BB
  attr
    office:value-type=string
2
  value=4
  attr
    office:value-type=float
    office:value=4

```

To convert this structure to L^AT_EX tabular code, you can use following function:

```

function tableToTabular(values)
  local rowValues = function(row)
    local t={}
    for _,column in pairs(row) do table.insert(t,column.value) end
    return t
  end
  content = {}
  for i,row in pairs(values) do
    table.insert(content,table.concat(rowValues(row)," & "))
  end
  return table.concat(content,"\\\\\\n")
end
-- Now use it with objects from previous example
print(tableToTabular(odsfile.tableValues(body)))

```

This example yields

```

Label & Position & Count\\
Hello & 1 & 3\\
World & 2 & 4\\
AA & 3 & 5\\
BB & 4 & 6\\
CC & 5 & 7

```

7 Changes

- v0.8**
 - added the escape option for enabling or disabling of the character escaping
 - fixed handling of merged cells in ranges
 - fixed escaping of backslashes
 - fixed row insertion

- v0.7**
 - Fixed character escaping. Unescaped “%, #, \$, _ and &” characters will be escaped to prevent compilation errors. Characters that are already escaped in the ODS file will be left untouched.⁴
 - Added support for LaTeX -recorder command line option
 - Added `celltemplate` option
 - Fixed named range handling⁵
- v0.6**
 - Fixed bug in handling of rows with only one cell⁶
 - Added support for named ranges
 - Fixed text:s handling. Beware that using multiple formatting styles in one cell may result in discarding whole cell, or wrong order. This is caused by underlying LuaXML library and it is likely to remain.
- v0.5**
 - Fixed bug: cell attributes weren't saved
 - Added support for merged cells
 - Added `multicoltemplate` option
- v0.4**
 - Fixed bugs in loading sheets without ranges
 - Fixed bugs in behaviour of empty cells⁷
 - Fixed bug in row counting⁸
 - Added support for children element in column paragraphs
 - Added cell value escaping
- v0.3**
 - Added support for multiline cells
 - Improved automatic column types generation
 - Added new options, `coltypes` and `columnbreak`
- v0.2**
 - LuaXML is now distributed as separate library, so other projects can use it.
 - New `AddRow` environment for adding data to the ods file
 - New command `\savespreadsheet` for saving ods file
 - Bug fixes: corrected loading of the sheets, corrected behaviour of blank cell
- v0.1** First version

⁴Thanks to Wybo Dekker

⁵Thanks to Angelforest

⁶Thanks to Ulrike Fisher

⁷Thanks to [TrippleWhy](#)

⁸Thanks to [yamsu](#)